



## CHARGE & OPERATE | POWERFUL

## MAKES IT BRIGHT

- Labino® TrAc Pack PRO UV lamps have unbeatable UV intensity, creating extreme excitation of fluorescent material, which makes it possible to see things, in daylight and at great distances, that was once impossible with former technology.
- The Labino® TrAc Pack PRO is a two-part lamp consisting of a luminary unit and a ballast unit (electronics and battery). There is also a Power Supply Unit (PSU) that makes it possible to operate the lamp while charging it.
- The lamp is available in three important distinctions – floodlight, midlight or spotlight – each giving different beams and intensities.
- The lamp obtains full power in 5-15 seconds and can be switched on and off, without the need for pre-cooling.
- The lamp is unaffected by magnetic fields.
- You can use the lamp outdoors, even in the rain, as the lamp is IP65 certified.
- Labino® TrAc Pack lamps are based on two key components – the Labino DUV-35 W Gas Discharge Bulb (MPXL technology) and the Labino Trigger Ballast (electronics). The interface technology between these key components creates unbeatable output performance.
- Manufactured in Sweden.



TrAc Pack PRO

## TECHNICAL SPECIFICATION

### Floodlight

Distribution angle (beam) approx. 45°  
Irradiance  $\approx 4\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Midlight

Distribution angle (beam) approx. 20°  
Irradiance  $\approx 12\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Spotlight

Distribution angle (beam) approx. 3.5°  
Irradiance  $\approx 45\,000\ \mu\text{W}/\text{cm}^2$  at 38 cm (15")

### Voltage

- Charger: 100, 115, 230 VAC
- Internal Battery: 12/24 VDC
- Input Power: 43 W
- Output Power: 35 W

### Weight

- Luminary Unit: 1.2 kilos (2.6 lbs)
- Battery and Electronic Unit: 4.4 kilos (9.7 lbs)
- PSU: 2.3 kilos (5.1 lbs)

### Cables

- Luminary & Battery/Electronic Unit: 2.3 meters (2.5 yd)
- Battery/Electronic Unit and PSU: 1.5 meters (1.6 yd)
- Cigarette Lighter Cable: 1.5 meters (1.6 yd)

### Battery

- 12 V, 7.2 Ampere, Lead
- Running time: 1.2 hours +/- 5%
- Charging time: 5-8 hours
- First time charge: 8 hours
- Charge from mains via Labino PSU 100, 115, 230 VAC
- Can be operated while charging

### Additional Information

- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 2 000 hrs
- Wavelength: UV-A, peak at 365 nm
- Start-up time: full power after 5-15 seconds
- Material in housing: anodized aluminium, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL, cETL approved
- IP65 classified, dust and temporary water jetting proof

DISTRIBUTOR:

Labino AB shall not be held liable for any errors or omissions resulting from the test procedures that were used in validating performance of any Labino AB product nor for unforeseen errors or omissions in digital or printed material.



**MAKES IT BRIGHT**